



GRABO DOMINO 2.0

| Technical parameter | Standard | Unit | Result |
|-------------------------|----------------|---------|--------------------|
| DESCRIPTION | | | |
| Constraction | | | Luxury Vinyl Tile |
| Plank size | EN ISO 24342 | mm | 185 x 1220 |
| | EN ISO 24342 | mm | 158 x 950* |
| Tile size | EN ISO 24342 | mm | 305 x 610 |
| Total thickness | EN ISO 24346 | mm | 2.0 |
| Wear layer thickness | EN ISO 24340 | mm | 0.3 |
| Total weight | EN ISO 23997 | kg/m2 | 3.0 |
| CLASSIFICATION | | | |
| European classification | EN ISO 10582 | class | 23 / 31 |
| Binder content | EN ISO 10582 | | Type I. |
| PERFORMANCE | | | |
| Abrasion group | MSZ EN 660-2 | class | T |
| Residual indentation | EN ISO 24343-1 | max. mm | 0.1 |
| Dimensional stability | EN ISO 23999 | max.% | 0.15 |
| <i>Requirement</i> | EN ISO 23999 | max.% | 0.25 |
| Curling | EN ISO 23999 | max. mm | 2 |
| Fire resistance | EN 13501-1 | class | Bfl-s1 |
| Slip resistance | EN 13893 | class | DS |
| | DIN 51130 | class | R10 |
| Chemical resistance | EN ISO 26987 | | ✓ |
| Light fastness | EN ISO 105-B02 | grade | 6 |
| Castor chair resistance | ISO 4918 | | ✓ |
| Surface treatment | | | iGUARD PUR Surface |
| Content of PCP | EN 12673 | | does not contain |
| Formaldehyde emission | ENV 717-1 | | E1 (no emission) |
| VOC | | | Pass |
| Warranty | Commercial | year | 5 |
| | Residential | year | 10 |