



GYMFIT 65

Property	Standard	Unit	Result
----------	----------	------	--------

DESCRIPTION			
Surface	X PUR Surface		
Backing	Closed cell PVC Foam		
Thickness	EN ISO 24346	mm	6,5
Top layer	EN ISO 24340	mm	0,7
Weight	EN ISO 23997	g/m ²	3600
Width	EN ISO 24341	m	2
Standard roll length	EN ISO 24341	m	20 ± 10%

CLASSIFICATION			
Product specification	EN 651 Vinyl floor covering for indoor sport purposes Meets the requirements of EN 14904 on sub-construction		
Impact sound insulation	EN ISO717-2	dB	16
Thermal resistance	-	m ² K/W	0,05
Reaction to fire	EN 13501	-	C _{fl} -s1

SPORT PROPERTIES			
Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	17
Vertical deformation	EN 14809	mm	0.33
Ball rebound	EN 12235	%	100
Specular gloss	EN 2813	%	< 30

TECHNICAL CHARACTERISTICS			
Dimension stability	EN ISO 23999	%	± 0,2
Indentation resistance	EN 1516	mm	<0,5
Resistance to rolling load	EN 1569	N	1500
Colour fastness	ISO 105 B02	-	6
Chemical resistance	EN ISO 26987	-	no change
Abrasion resistance	EN ISO 5470-1	mg/1000cycles	< 250

OTHERS



3338



6170



7483



2519-371

Warranty:



Hygiene:



Cleanability:



Environmental attributes:



No periodic renewal needed. Solvent and heavy metal free.

GRABOPLAST Floor Covering Manufacturers Ltd.

H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100

mail@graboplast.hu www.graboplast.hu