

GRABO MOD-FLEX ACTIVE

Technical datasheet

Technical parameter	Standard	Unit	Result
DESCRIPTION			
Size of tile	EN ISO 24342	mm	1000 x 1000 ± 20
Total thickness	EN ISO 24346	mm	15 ± 1
Guarantee	-	years	2
Material	Recycled SBR rubber granulate with PU binder		
Feature:	Slippage resistant, water resistant, rot proof, frost proof		
Installation:	Upon indoor smooth floor without or with adhesive		
Available colours	SBR black, EPDM Mix coloured		
PHYSICAL AND MECHANICAL CHARACTERISTICS			
Module weight	EN ISO 23997	kg/pcs	14,9 ± 0,5
Total weight	EN ISO 23997	kg/m ²	14,9 ± 0,5
Tensile strenght	EN ISO 527-4	N/cm ²	121,5
Hardness Shore A (Sh°)	EN ISO 527-4	A (Sh°)	65 ± 70
Elongation	EN ISO 527-4	A (%)	83,3
Flame resistance	DIN 4102/1	15 seconds	No flammability exceeding 150 mm
Friction/slippage resistance	TS 659 A		excellent
Environmental resistance:	ISO 14001		rot-proof and water-resistant
GRABOPLAST Floor Covering Manufacturers Ltd. H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100 mail@graboplast.hu www.graboplast.hu			